



# NF 024

## Microlitre Centrifuge



- One compact centrifuge offering two different rotors for wide range of applications requiring high speed and xg force
- Programmable microprocessor control system for accurate and reliable operations
- Large back-lit LCD display for easy reading of all parameters
- Possibility of programming RCF
- Pulse key for short centrifugation requirements
- Reduced temperature increase in the chamber by means of continuous air cooling
- Quite brushless maintenance free DC motor
- Dual shell metal enclosure
- Imbalance detection system
- Delivered with 12x1,5/2 ml. angle rotor and adaptors for 200  $\mu$ l and 400/500  $\mu$ l microtubes

## TECHNICAL SPECIFICATIONS

Maximum speed	15.000 rpm
Maximum RCF	15.596xg
Tube capacity	12 x 1,5/2 ml
Control system	Programmable Microprocessor Control
Speed set range	500 - 15.000 rpm
Speed set step	100 rpm
Timer set range	30 seconds-999 minutes and hold position
Motor	Brushless DC motor
Body, lid and chamber	ABS plastic reinforced by metal enclosure
Power Supply	24 V DC
Power Consumption	72 W
External Dimensions (WxDxH) mm.	262x230x131
Packing Dimensions (WxDxH) mm.	340x 300x195
Net / Packed weight (kg)	4 / 6

## OPTIONAL ROTOR

Z12. B 02 083 Angle rotor, 2x8x0,2 ml PCR Strip 15.000 rpm. 13.080xg



**NUVE SANAYİ MALZEMELERİ İMALAT VE TİCARET A.Ş.**

Saracalar Mah. Saracalar Kümeevleri No: 4/2 Akyurt 06750 ANKARA / TURKEY t. +90 312 399 28 30 f. +90 312 399 21 97

[nuve.com.tr](http://nuve.com.tr) [sales@nuve.com.tr](mailto:sales@nuve.com.tr)

ISO 9001: 2008  
ISO 13485: 2003

